

Computation Model of Electrostatic Spraying in Agriculture Industry

Murtadha Al-Mamury¹, Wamadeva Balachandran¹, Hamed Al-Raweshidy¹, Nadarajah Manivannan¹

¹Brunei University, Uxbridge, UK

Abstract

Introduction: Agricultural chemical such as pesticides are used to protect plants against insects and diseases. Electrostatic spraying can be used for an efficient use of pesticide [1][2]. In this project, electrostatic spray is investigated with intelligent sensors for efficient use of pesticides. As a part of this project, COMSOL Multiphysics® model was developed to understand spray properties, in terms of electric field distribution. In particular, FEM model was developed to investigate electric field distribution for charged droplet and grounded targets. Five different shapes of targets (conical, spherical, cylindrical, flat and ellipsoid) were investigated. COMSOL Multiphysics® model: Electric static model (es) in the COMSOL Multiphysics® software was used to simulate our FEM model. The figure below shows the COMSOL Multiphysics® model developed; showing charged droplet, grounded target and grounded boundary box. Size of charge droplet size is 33 μm and surface charge density is $137.5 \text{ E-}12 \text{ C/m}^2$. These parameters were obtained from our experimental work carried out in Brunel University, UK. The height of targets used is 20 cm and the volume of the boundary box is one cubic meter due representing the Faraday cage.

Figure 2: COMSOL Multiphysics® Model of charged droplet and grounded target
COMSOL Multiphysics® finite element model (FEM) was solved for the following equations:
Where: E = Electric field (V/m), ϕ = Electric potential (V), ϵ_0 =Permittivity of free space = 8.854×10^{-12} (F/m), ϵ_r =Relative permittivity of the air 1.0005, and ρ_v = Density of droplets $.103(\text{kg/m}^3)$.

Results: The electric filed distribution of the charged droplet-target model for Ellipsoid target is shown in the Figure 2. The maximum electric filed achieved, charged-to-mass ratio and induced current in the targets are summarized in the table 1. Conical shaped target generates highest electric field and a rounded target generates the least electric field. These results will be used in our intelligent sprays so that amount of pesticides can be controlled based on the shape and size of targets.

Type of target Maximum electric field (V/m) Charged mass ratio (mc/kg) Current in the target (μA)

Conical 61.524 14.6 14.892

Flat 24.932 14.2 13.206

Cylindrical 19.928 13.700 11.645

Ellipsoid 17.662 11.8 8.968

Spherical 17.255 8.3 5.694

Table 1: Various targets and their parameters

Conclusion: COMSOL Multiphysics® FEM model was developed and simulated to identify the electric field distribution and induced current on different five shapes of grounded targets for a fixed charged water droplet. The results obtained in this work will be used to design and implement smart sprays with sensors to improve the efficiency of the use of pesticides.

Reference

References

- [1] Mamidi, V.R., C. Hansyam. P.M., Kumar .and P.Kapur “Electrostatic hand pressure knapsack spray system with enhanced performance for small scale farms”. J. of electrostatic. 1 (1-6). (2013).
- [2] Roten, Hewitt, Ledebuhr, Thistle, Connell, Wolf, Sankar and Woodward Evaluation of spray deposition in potatoes using various spray delivery systems”. New Zealand Plant Protection 66: 317-323 (2013).

Figures used in the abstract




Figure 1: COMOL Model of charged droplet and grounded target




Figure 2: Electric Field distribution